

## WEISSCAM HS-2 Digital Highspeed Camera



## WEISSCAM HS-1 & HS-2 Digital Highspeed Camera

The WEISSCAM HS-1 was successfully launched worldwide in summer 2006.

In spring 2009, P+S Technik delivered the follow up model HS-2 to the world market. More information on the HS-2 you can find on the following pages of this catalogue and on our website [www.pstechnik.de](http://www.pstechnik.de)

For information where to rent WEISSCAM Services, please visit our website [www.pstechnik.de](http://www.pstechnik.de) and use the link in the top menu to go to the rental section. Select WEISSCAM and then your region to get a complete list of the WEISSCAM Rental Stations in your region !


For more information about becoming a WEISSCAM Rental Station, please contact P+S Technik by email to [WEISSCAM@pstechnik.de](mailto:WEISSCAM@pstechnik.de).




## WEISSCAM HS-2

Artikel No.	Description	Price in €
25713	<p><b>WEISSCAM HS-2 "basic camera" with 32GB RAM Buffer Content</b>            WEISSCAM HS-2 Camera Body with 32 GB RAM            incl. IMS-Mount 35mm camera adapter plate (#21842)            two handgrips large (#25026)            WEISSCAM HS-2 Camera User Manual (25801)            IMS PL-Mount (#18431)            WEISSCAM HS-2 Camera Control Software (XP based) (#24431)            WEISSCAM AC/DC Power supply unit (110-230 Volt/24Volt, 320 Watt) (#24430)            incl. power supply cable for camera body (24V, 4pin/XLR/m - 2pin Fischer/f) (#25798)</p>	
<p><b>HS-2 stand alone package</b>   <b>Master quote 801166 / 900152</b></p>	<p><b>WEISSCAM HS-2 "stand alone" with 32GB RAM Buffer Content</b>            WEISSCAM HS-2 Camera Body with 32GB RAM            incl. IMS-Mount 35mm camera adapter plate (#21842)            two handgrips large (#25026)            WEISSCAM HS-2 Camera User Manual (#25801)            IMS PL-Mount (#18431)            Electronic Viewfinder, incl. 3-axis adjustable holder, eyepiece, eyepiece cup and cable (#23079)            WEISSCAM HS-2 HU-2 Hand unit, incl. touch screen and control software for HS-2 (#24429)            Hand unit cable, CBUS cable 0,8m (#19917)            WEISSCAM HS-2 Camera Control Software (XP based) (#24431)            WEISSCAM AC/DC Power supply unit (110-230 Volt/24 Volt, 320 Watt) (#24430)            incl. power supply cable for camera body (24V, 4pin/XLR/m - 2pin Fischer/f) (#25798)            WEISSCAM DM-2 DigiMag Recording Unit for HD-SDI single and dual link connection and WEISSCAM RAW compatible, 24V DC, incl. power supply for Digi Mag (#25795) and DC cable, 4p/XLR/m - 4p/XLR/f (#25799)            WEISSCAM DM-2 DigiMag User Manual (#25802)            WEISSCAM HS-2 Camera Case (#24433): fitting camera body, hand unit, viewfinder, cables, IMS PL-Mount, two hand grips large            WEISSCAM DM-2 DigiMag Case (#24434): fitting DM-2, DBB Debayerbox, cables, AC/DC power supply for each HS-2 camera, DM-2 and DBB</p>	

## Individual Options

Artikel No.	Description	Price in €
24435	<b>WEISSCAM DM-2 DIGIMAG Recording Unit</b> for HDSI single and dual link connection (YCC 4:2:2, RGB 4:4:4) and RAW Data, 24 V DC, incl. power supply for DM-2 (#25795), DM-2 User Manual (#25802)	
25984	 <b>Electronic Viewfinder for WEISSCAM HS-2,</b> incl. 3-axis adjustable holder, eyepiece, eyepiece cup, incl. cable (Lemo 4 pin, VGA), DVI adapter	
24427	<b>Optical Viewfinder</b> for IMS camera mounts and PL lenses (delivery estimated 2010)	
24428	<b>WEISSCAM HS-2 DBB External Debayerbox for HS-2 and DM-2</b> allows debayering of HS-2 RAW Data into HD-SDI YCC incl. power supply 110-230V and cables Input/Output: BNC connector	
26038	<b>WEISSCAM HU-2 Hand Unit</b> incl. touch screen, control software for HU-2 and HU-2 User Manual  For wire control solution: WEISSCAM HU-2 hand unit cable is recommended For wireless control solution: Cmotion Camin is recommended	
19917	<b>WEISSCAM HU-2 Hand Unit Cable, 0,8 m</b>	
19851	<b>WEISSCAM HU-2 Hand Unit Cable, 6,0 m</b>	
25985	<b>WEISSCAM HU-2 Flex Arm</b> incl. flex arm 1/4" screw to rosette and hand unit adapter 1/4" to 3/8"	

## Cables

Artikel No.	Description	Price in €
24430	<b>WEISSCAM AC/DC Power supply unit</b> 110-230 Volt / 24 Volt , 320 Watt	
17236	 <b>Power supply cable</b> 24V, 2-pin Fischer to 3-pin XLR	

## Software

Artikel No.	Description	Price in €
24431	<b>WEISSCAM HS-2 Camera Control Software (XP based)</b>	
24432	<b>WEISSCAM HS-2 Batch Render Software ( XP based)</b>	

## Cases

Artikel No.	Description	Price in €
24433	<b>WEISSCAM HS-2 Case</b> fitting HS-2 camera body, IMS-PL Mount, hand unit, viewfinder, cables, two hand grips large	
24434	<b>WEISSCAM DM-2 case</b> fitting for DM-2 DIGIMAG, Debayerbox DBB, cables, AC/DC power supply for each: HS-camera, DM-2 and DBB	

## Training

25800	<b>WEISSCAM HS-2 Training</b> 8 hours training day for 4 operators The HS-2 training should take two days and is held by a high-speed specialist of P+S Technik / WEISSCAM. HS-2 owners get special rates. If the training is not held at P+S TECHNIK, the cost for travel and appropriate accomodation have to be paid by the customer. Travel days will be charged with 50%. All necessary equipment has to be organized by the customer. Administrative items as travel scheduling and flight booking are done by P+S TECHNIK staff.	
-------	--	--